



BAUER Group

P.T. BAUER Pratama Indonesia



FULL DISPLACEMENT COLUMN

An Optimum Geotechnical Solution to
Support Embankment on Soft Soil

10th Business Forum

Road Engineering Association of Asia and Australia

Labuan Bajo, Nusa Tenggara Timur - Indonesia

Antonius Setiawan, Yasin Widodo, Idrus M. Alatas, Agus Himawan.


25 August 2023

1

Introduction




Distribution of Soft Soil in Indonesia (Wardoyo et al., 2019)



- Indonesia, as a tropical country, has a significant distribution of soft soil, including soft clay, peat, and organic soil, covering approximately 60 million hectares or about 30% of the country's land area.
- With around 20 million hectares consisting of peatlands and organic soil.


Introduction



- In Indonesia, embankment works such as roadways, runways, and flood control embankments, are still the most selected option for elevating infrastructure works.
- Constructing embankments on soft soil deposits poses a challenge:
 - Low shear strength
 - High compressibility characteristics.
 - Long-term consolidation of fibre in peat and organic soil, as well as pore compression resulting from loading.

Note

	Soft Clay		Peat and Organic Soil
--	-----------	---	-----------------------




Concepts:

- The pile support method does not fundamentally improve the physical and mechanical properties of soft soil.
- A significant portion of the embankment load is transferred to the piles through a Load Transfer Platform (LTP) by arching mechanisms, while the remaining load is carried by the soft soil between the piles, resulting in consolidation settlement and negative skin friction (NSF) on the piles.
- Long-term settlement can be reduced.
- Further reduction in soil settlement can be achieved by incorporating high-tensile geotextiles

Introduction



Load distribution → The vertical loads of the system are distributed into 3 load parts



- **Parts A:** Load is transferred directly to piles
- **Parts B:** Load goes through the geosynthetics to the piles
- **Parts C:** Load is carried out by subsoils

(van Eekelen, 2015)

2

Full Displacement Column



Principles of Ground Improvement Technique



Ground improvement methods are used to improve unsuitable subsurface soils and/or to improve the performance of structures or embankments.

These methods are used when replacement of the in-situ soils is impractical because of physical limitations, environmental concerns, or other conventional methods are costly.

Functions:

- Increase bearing capacity, shear, or frictional strength,**
- Increase density,**
- Control deformations,**
- Increase or provide lateral stability,**
- Form seepage cutoffs or fill voids,**
- Transfer embankment loads to more competent layers, and**
- Increase resistance to liquefaction.**



Principles of Ground Improvement Technique




Inclusion / Reinforcement

Techniques that introduce foreign elements to improve in situ soil




Consolidation

Techniques that drain and reduce voids



Compaction

Techniques that densify soil by compaction



Principles of Ground Improvement Technique



Improvement by Inclusion/Reinforcement

Vibro Stone Column	Vibro Concrete Column	Cutter Soil Mix
Soil Cement Column	Dynamic Replacement	Full Displacement Column
Grouting		

Improvement by Consolidation

Prefabricated Vertical Drain

Improvement By Compaction




Vibro Compaction

Dynamic Compaction



The Technique

Advancement of a displacement boring tool into the ground with a rotary drilling rig using both torque and crowd force



Full Displacement Column

Full Displacement Column (FDC) is a rigid inclusion method developed by BAUER.


This ground improvement method is constructed through introducing the displacement tool to the soft soil formation and injecting a rigid material to be formed as a column by cast-in-place mortar grout which is constructed by a rotary drilling technique that is installed in certain grids (square or triangular pattern).



Full Displacement Column



Range of application




Full Displacement Column

Range of Application

Compared to other ground improvement technique, FDC has wider range of application. It perform very well in soil conditions ranging from sand/gravel, silt and clay to soft organics soils, as long as the soil is displaceable.

The general rule of thumb applies: $SPT < 30$ or $CPT < 10$ Mpa, undrained shear strength $c_u > 15$ kN/m², and non-displaceable layer with thickness < 1.50 meter.



(Messe, 2017)

Full Displacement Column

Main Equipment



DISPLACEMENT TOOL

Post-densification during extraction

Counter-rotating flight on a conical body for densification of any loose soil areas during extraction of the tool

Stabilisation

Cylindrical displacement body for stabilisation of the displaced soil material

Densification

Conical shape of the hollow stem induces horizontal forces in the soil conveyed upwards by the flight (horizontal densification energy)

Loosening

The soil is loosened by the starter auger section and conveyed upwards by the flights



FDC Rig




EXCAVATOR




MORTAR PUMP

Full Displacement Column


Construction Sequence



FDC - Sequence of Works



FDC - Sequence of Works (animation)




Full Displacement Column

Typical Site Setup

Rigid material (concrete or mortar) is pumped using moveable concrete pump through the supply lines which is connected to the hollow rods and discharged at the outlet on the bottom of displacement tool.



Workability of concrete/mortar normally within 55-70 cm (slump flow)




Full Displacement Column

Reinforcement in FDC

- In the nature of ground improvement design (i.e. to improve bearing capacity and settlement control), reinforcement is not necessary to be installed.
- Reinforcement is needed when the FDC designed to counteract uplift or mitigate excessive lateral forces impacting the specific footings of embankment or any other structures.
- Installation of reinforcement is conducted immediately after mortar is pumped into the column.



*Jumlah kolom FDC pada gambar hanya sebagai ilustrasi




(a)

(b)

Advantages



- ▶ Increase of skin friction and toe resistance due to compaction
- ▶ Vibration free installation method
- ▶ High daily performances
- ▶ Negligible spoil carriage
- ▶ No surcharge required



3



Illustration Stages of Construction an Embankment Supported by Full Displacement Columns



Stages of Construction



FDC Installation




Stages of Construction



Installation of Load Transfer Platform

Load transfer platform
incorporating with geotextile




Stages of Construction



Installation of Fill Embankment


Fill material installed layer by layer with proper compaction



Stages of Construction



Completed Embankment and Pavement



4

Innovation in BAUER and Implementation Technology 4.0



Innovation in BAUER




BAUER BG 1



1790

- 1790 Foundation as a copper forge in Schrobenhausen, Germany
- 1870 Artesian well for the new Schrobenhausen railway station, start a drilling work
- 1976 First hydraulic rotary drill rig BG 7
- 1984 First diaphragm trench cutter BC 30
- 2014 New generation machine with EEP



1870




1976



1984



2014



Bauer Assistant Systems

- Extended assistant and automatic systems offer numerous advantages for many different drilling techniques
- Reduction in wear on both machine and drilling tool
- Increase in productivity



Communication Technology

- Bauer B-Tronic system with high-resolution touch screen for display of main parameters
- Tablet with standard Internet connection for accessing the drilling rig. The operator's screen can be mirrored live on the tablet and the operator has the option to access manuals, machine management data and more
- Due to machine networking, production data, locations and detailed reports of drilling operations can be retrieved from isolated machines as well as the entire machine fleet




The Intelligent Rotary Drilling Rig



B-Tronic

The B-Tronic system delivers a complete system that goes far beyond the electronic control of the machine.

The B-Tronic system assists to complete the construction activities reliably and accurately.



The high-performance B-Tronic system based on dozens of sensors that positioned at all critical points in the machine. These sensors continuously collect data which are centrally logged and processed.



A high-resolution touch screen with a range of different display modes inform the operator about the status of the machine and provide details for its optimum use.


Data transmission system such as WLAN, USB, or the DTR communication module, allow the machine and production data to be transmitted locally and globally to any point via the internet.

Tracking of Process Data Using B-Tronic Activity (B-Report)



B-Tronic Activity is a software program that records the activity of drilling rigs and combines it with equipment data already captured.


B-Tronic Activity (B-Report)




The entire production process no longer has to be compiled using individually recorded work steps assembled from equipment data and manual logging
→ **a time consuming and complex task.**

Once the digital information for a sufficient number of projects has been entered in a central database, it can serve as a valuable basis for costing purposes or handling follow-up work.

B-Tronic Activity (B-Report)




Analyzing



Print out / Report

B-APS (Assistant Positioning System)



GPS positioning in specialist ground improvement / foundation engineering,

GPS has now also found its way into specialist ground improvement / foundation engineering and facilitates the accurate positioning of drilling rigs in the respective drilling points.

B-APS (Assistant Positioning System)



B-APS, the Assistant Positioning System uses two GPS antennas to detect the current position of the drilling rig and the display then guides the operator to the planned drilling sites.

The simple and fast process increases the device's productivity and brings additional time and cost savings.

B-APS (Assistant Positioning System)

Real time to tracking the position of each machine and its activities such as current position, daily sequence, and activity inside the operator's cabin.

The screenshot displays the Bauer WEB-BGM monitoring interface. The top navigation bar includes the text "Bauer WEB-BGM", a "Reload in 11:48" indicator, language selection ("English"), and user information ("Yasin Widodo"). A left sidebar menu lists options: Monitoring, Dashboard, Equipment, File Explorer, B-Report, B-Activity, and Contact. The main content area is titled "Control Center" and features a search bar and a filter section. Below this is a table of equipment:


Type	Num.
BG-42-V	18
BG-48-V	661
BG-28-V	805
BG-40-V	954
BG-40-V	1312
BG-40-V	1343
BG-40-V	1944
BG-40-V	2248
MC-64	164
BG-40-V	2563
BG-40-V	2572
BG-40-V	2701
BG-40-V	2827
BG-40-V	3036
BG-28-V	2842
BG-40-V	3038

The central control panel for machine ZA-G43 displays the following data:

- Depth: 1,70 m
- Crowd speed: 0,00 m/min
- Pressure: 0,12 bar
- Concrete volume nominal (+ 0 %): 0,00 m³
- Concrete volume start (Start: 0,2 bar): 1,71 m³
- Strokes: 59
- Torque: 0 %
- KDK 1: 0 1/min
- Mast inclination: -0,6 °
- drilling: -0,2 °

Two graphs are shown: "Penetration-resistance" and "Penetration-rate". The "Penetration-resistance" graph shows a sharp peak at approximately 1,70 m depth. The "Penetration-rate" graph shows a corresponding peak at the same depth. A "Job site data" sidebar on the right includes buttons for "Start", "File administration", "Crowd assistant", and "Inter-ruption". A legend at the bottom right indicates status indicators: Active Equipment (blue), Motor ON (green), Service required (orange), and Critical error (red). The bottom of the screen shows a Windows taskbar with the search bar and various application icons, along with the system clock showing 2:08 AM on 10/4/2020.

Digitization of construction site processes with BIM




Visualization of the planning through the use of BIM – e.g. for the work at the Herbert Hoover Dike

Complex construction projects are nowadays digital right from the beginning. A fact that lead to fundamental changes in the process not only in structural engineering but also in specialist foundation engineering. Lengths, widths, and heights are recorded.

Likewise: when will something be built and what does it cost?


All of this together called Building Information Modeling or BIM

Further Development




Source: aproplan.com



Identified of critical part



Clash detection warnings



Quantity survey, time schedule and cost estimation





Jakarta Airport, Indonesia

CONFIDENTIAL AND PROPRIETARY

Please be noted that all concepts, designs, calculations, drawings, and presentations submitted by BAUER are the property rights of BAUER. All rights reserved. Any use of these materials without specific written permission and consent of BAUER is strictly prohibited.



*PASSION for
PROGRESS*

Thank you



Questions?

Contact

YASIN WIDODO – Business Development Manager

P.T. BAUER Pratama Indonesia

Alamanda Tower 19th Floor,

Jl. TB Simatupang Kav 23-24

Cilandak Barat – Jakarta Selatan 12430

Phone 021-29661988

Fax 021-29660188

Email yasin.widodo@bauer.co.id, bauerina@bauer.co.id