


Sustainable Road Construction: Advancements in Cement Product as Key Enabler

10th Business Forum Road Engineering Association Of Asia and Australasia





OUTLINE



Go Beyond Next



OUTLINE



Go Beyond Next



THE CHALLENGES OF TODAY'S ROAD INFRASTRUCTURE



Building a good city requires good infrastructure.



The road network in Indonesia is a vital public infrastructure that connects all parts.



The construction industry is currently facing many problems and challenges

The following are some of the challenges in Indonesia's road infrastructure development:



Poor Pavement Structure



Unstable Material Quality



Unstable Soil



Road Structure Complexity Increases



Vulnerable To Flooding



Environmental Impact of Construction



Inconvenience During Maintenance And Repair Work



Inconsistent Work Results

....... as a material supplier, SIG will be an integrated solution provider to overcome the problems and challenges of road construction in Indonesia.



OUTLINE



Go Beyond Next



SIG PROFILE & COMMITMENT

We Are Now the Solution Provider

SIG aims to be at the forefront of providing innovative, applicable and value-added building material solutions in the region.

National Distributio n Coverage	9 integrated plants, 6 grinding plants and 30 Packing plants spread from Sabang to Merauke.
43 % Capacity Share	70% utilization. 76% green cement production.
Diverse & Green Label	Complete diversification of cement, mortar and concrete products based on construction uses
Product	Green label product with lower carbon emission: PwrPro, EzPro, DuPro+ LH, DuPro+ SBC, Maxstrength
Footprint PSN	YTD 2022 SIG has contributed to 148 National Strategic Project (PSNs) and we are committed to do more.
Domestic	Cement Product TKDN value of up to 98.6%*.
Component Level (TKDN)	*Certified by Sucofindo

50% 2021 National market share

51%
Government
Shares







Grinding Plants

Dumai Riau 1 unit

Cement Mill

Palembang South Sumatra

1 unit Cement Mill Bandar Lampung Lampung 1 unit

Cigading WestJava 1 unit

EastJava 1 unit

Gresik

Ho Chi Minh Vietnam

1 unit Cement Mill



PP Packing Plants

In 30 locations



Dumai

Tuban

Gresik

30.000 DWT **Teluk Bayur** 40.000 DWT **Palembang** 8.500 DWT Cilacap 40.000 DWT 40.000 DWT 20.000 DWT Biringkassi 40.000 DWT **Quang Ninh** 20.000 DWT Ho Chi Minh 15.000 DWT





Lhoknga Aceh

1 Cement Kiln and 2 Cement Mills

Capacity

lion tons

Indarung **West Sumatra**

5 Cement Kilns and 8 Cement Mill

Million tons per year

Baturaja **South Sumatra**

2 Cement Kilns and

3 8 Sillion tons

Narogong West Java

Quang Ninh, Vietnam

2 Cement Kilns and 6 Cement Mill

Million tons per year

Cilacap Central Java

1 Cement Kilns and 2 Cement Mill

Capacity

Million tons

Rembang **Central Java**

1 Cement Kilns and 2 Cement Mill

Capacity

Million tons peryear

Tuban East Java

6 Cement Kilns and 11 Cement Mill

SIG Capacity

3 Sillion tons

Tonasa South Sulawesi

4 Cement Kilns and 6 Cement Mill

Capacity

Million tons er year

Quang Ninh Vietnam

1 Cement Kilns and 2 Cement Mill

Capacity

2 Suta ton



SIG'S COMMITMENT TO SUSTAINABLE LIVING

INTEGRATING SUSTAINABILITY STRATEGY

DRIVING SUSTAINABLE SOLUTIONS AND INNOVATION

Promote sustainable products and solutions



49% proportion of sustainable products and integrated services solutions to total revenue

Rembang Plant

Sustainable procurement



75% long-term contract value to total purchases (goods/services)

盡

100% of active contractors screened via CSMA

PROTECTING THE ENVIRONMENT

Climate and Energy



27% scope 1 GHG emissions reduction from 2010 baseline

Biodiversity



100% biodiversity management plans implementation



1.87 million alternative raw material

0.9 million tonnes of alternative

Air emissions



25% dust emissions reduction from 2019

Water management



11.46% reduction of specific freshwater withdrawal (L/tonne cement eq.) from 2019 baseline

Community development

CREATING VALUE FOR PEOPLE AND

COMMUNITY



8.6 million beneficiaries cumulative since 2015

Occupational health and safety



0.33 Lost time 0 fatality injury frequency rate (LTIFR)

Ethics and compliance



100% compliance on code of Conduct

Employment



Availability of top talent with global leader quality








SIG'S COMMITMENT TO SUSTAINABLE LIVING

DECARBONISATION EFFORT

CO₂ Emission Intensity, Scope 1 – From Internal Process (KgCO₂/Ton cement eq.)

Decarbonisation Initiatives related to GHG Reduction - Scope 1



Increasing Alternative Fuel & Raw Material (AFR)
Use

Optimising Specific Thermal Energy Consumption (STEC)


Producing Excellence Products

- Substitution of extractive material with non extractive material
- Collaboration with PENTAHELIX scheme to optimise the use of the green products and solution

CO₂ Emission Intensity, Scope 2 – From Indirect Use of Electricity

(KgCO₂/Ton cement eq.)

Decarbonisation Initiatives related to GHG Reduction - Scope 2



Optimising Renewable Energy Supply

- ➤ Solar Panel installation via Partnership with local provider—Scheduled to scale up by 7.5 MWp in 2023 with target 572 Mwp in 2030
- Solar Panel will be installed in all plant across Indonesia (SIG Tuban, SBI, SP, ST, SG, SMBR and IKSG)
- Other renewable initiatives such as optimise use of existing waste heat recovery power generator (WHRPG) with 29.5 MW installed capacity









SIG'S COMMITMENT TO SUSTAINABLE LIVING

DECARBONISATION EFFORT



Production Excellence



Lean Manufacturing (Eliminate Waste)



Advance Process Control



Utilisation of AFR (Non Extractive Material)



Sustainable Supply Chain



Applied Research & Innovation



Technology Digitalisation



Renewable Energy

ADVANTAGES

ECONOMIC BENEFITS


- Potential savings of 5-15% on cement costs
- Efficient repair costs due to durability


TECHNICAL BENEFITS


- · Allows for a more precise and accurate selection of cement according to requirements and environmental conditions
- · Compressive strength growth continues even after 28 days of age
- · Better durability, so the life of the structure can be extended
- · Consistency of product quality is more controllable compared to manually adding a third material when making concrete in the field.
- Have the ability to achieve much higher final compressive strength, so there is potential for slimmer structural dimensions.

ENVIRONMENTAL BENEFITS

- Contribute to government programs to reduce CO2 emissions
- · Support the use of waste materials from other industries (fly ash & GBFS)
- Supporting the implementation of green infrastructure programs







drymix industry.


8% lower emissions*

initial setting time*

- heat*
- TKDN: 96.99%



SNI 7064:2014



- hydration heat*
- 28% lower emission*
- Strong & smooth finish
- ► TKDN: 96.95%



PWRPRO

8912:2020

SNI

(HE)

CEMENT

MAXSTRENGTH SNI 8363:2017

- High rise building, fly over and tunnel construction applications
- 25% lower hydration heat*
- Permeability is 19% better*
- Sulfate resistance is 92%*
- Chloride resistance is 85%*
- ▶ 16% lower emissions*
- TKDN: 89.98%



0302:2014

DUPRO+ LH



SNI 0302:2014 (IP-K)

DUPRO+ SBC

- Construction applications in marine waters, power plants, smelters, waste water lines
- 11% lower hydration heat*
- Permeability is 20%*
- Sulfate resistance is 72%*
- DUPRO+ LH: 16% lower emissions*
- DUPRO+ SBC: 22% lower emissions* TKDN: 91.39%
- *) than conventional production process



CEMENT

MULTIPURPOSE

SNI 3758-2004

- Affordable prices and guaranteed quality
- Mix fluffier and dry time just right
- Better adhesion
- Minimal cracking and peeling
- 37% lower emission*




SNI 7064:2014

- Easier to work with, and more watertight
- Lower temperature of concrete so it doesn't crack easily
- Higher concrete strength without additional additives
- Concrete dries 30% faster
- Concrete is 15% stronger
- ▶ 8% lower emissions*



SNI 7064:2014

- better adhesion, easier to work with, and more watertight
- Lower temperature of concrete so it doesn't crack easi the end result is stronger and the surface is smoother
- masonry work (parting, plastering, plastering)
- environmentally friendly cement
- 28% lower emissions*





ORDINARY PORTLAND CEMENT

SIG PRODUCT & SOLUTION

UltraPro

SprintPro

DuPro+ HSR

DuPro+ MSR

SuperTermo

SNI 2049-2015 - Tipe I

SNI 2049-2015 - Tipe I

SNI 2049-2015 - Tipe V

SNI 2049-2015 - Tipe II

API Spec 10A Class G-HSR



- High early and late strength
- Optimal Dry Time
- · Better Flexural Strength
- Sturdy Final Results
- Cement based Soil stabilization



- Higher early Compressive Strength
- Optimum Hydration Process and Maintained
- High Productivity
- The End Result Is Not Easy to Crack
- · Cement based Soil stabilization



- · High sulphate resistance
- Moderate chloride resistance
- · Better permeability of concrete
- Higher and longer lasting initial & final press tips



- The resistance to sulfates and chlorides is moderate
- · Better permeability of concrete
- Higher initial & final compressive strength and long lasting



- Consistent Quality and Response to Additives
- Sulfate Resistance and Stable Performance At High Pressure
- Cement Rheology According to Application















ROAD RESEARCH & DEVELOPMENT COLLABORATION

TO MEET FUTURE BUSINESS CHALLENGES

Porous Concrete Application on the Road Material Technology Application Trial Project (mini circuit) Porous Concrete Application on the glass bridge project, National Tourism Strategic Area (KSPN) Bromo-Tengger-Semeru, East Java

Development of high performance concrete using hydraulic cement (SNI 8912:2020)

Development of Soil stabilization

Directorate of Road and Bridge Engineering, Directorate General of Highways, Ministry of Public Work

East Java Regional Residential Infrastructure
Centre, Directorate General of Human
Settlements, Ministry of Public Work

BRIN

National Research and Innovation Agency (BRIN) and Chemical Additive Manufacturer



Taiheiyo Cement Corporation (TCC)



Development of an environmentally friendly geopolymer based on fly ash as a non-shrinking grout

University of Indonesia (UI)



Self Healing Concrete for Prevention and Repair of Concrete Cracks



Rapid Strength Concrete (RSC) Rigid Pavement as an environmentally friendly road construction solution based on a case study of national road repair in the Duduk Sampeyan - Lamongan area.



National Research and Innovation Agency (BRIN)



East Java-Bali National Road Implementation Centre, Directorate General of Highways, Ministry of Public Work











RESEARCH AND DEVELOPMENT CAPABILITY

RESEARCH FACILITIES

R&D SIG Holding

- Physical laboratory
- Chemical Laboratory (Instruments)
- Chemical Laboratory (Wet)
- Concrete and Bulding Materials Laboratory
- Soil Laboratory

Research Center Narogong

- Cement Laboratory
- Concrete Laboratory
- Housing and Building Materials Laboratory
- Soil Laboratory

Laboratory of Concrete Subsidiary

· Concrete Laboratory

Laboratory of Cement Subsidiary

Cement Laboratory

PARTNERSHIP AND **COLLABORATION**

Universities

External Laboratory and Research Institution

Chemical Products Companies

Construction Companies

Consultant Companies

Government and Association

FIELD OF R&D

Raw and Alternative Materials

Cement Products

Cement Derivative Products

Packaging

Spareparts

Application Test

QUALIFICATIONS AND CERTIFICATIONS

QUALIFICATIONS

Chemical Engineer, Civil Engineer, Material Engineer, Mechanical Engineer, Chemist, Analyst

CERTIFICATIONS

International and Domestic

OUTPUT RESULTS OF RESEARCH

(2017 - 2022)

Product Development

77

Process Development

16

Material & Application Test

X-Ray Diffraction, XRD



UV Spectrophotometer



Vertical Mill

X-Ray Fluorescence, XRF





Bomb Calorimeter



Heat of Hydration Calorimeter



Roller Screed



Compression Testing Machine 2000 kN Capacity



Mini Ball Mill



*ISO17025 accredited lab

Paving Machine

*example of R&D Equipment



OUTLINE



Go Beyond Next



ENVIRONMENTAL FRIENDLY SOLUTIONS FOR SUSTAINABLE ROAD INFRASTRUCTURE

SIG PRODUCT & SOLUTION

RAPID STRENGTH CONCRETE (SpeedCrete)

As an effort to minimising road traffic issues and reducing CO₂ emissions, PT Semen Indonesia (Persero) Tbk (SIG) as a leading multinational building material solution company has presented Rapid Strength Concrete (RSC) as one of the solutions to the problem of reducing the duration of concrete pavement. Fast track pavement concrete solution with guaranteed open traffic 3-12 hours after concrete finishing and maintenance period. SpeedCrete has proven to be effective in reducing congestion caused by road repairs in high traffic areas.

PARTNER

- Directorat General of Highways East Java & Central Java, Ministry of Public Work
- Directorat General of Human Settlements
 Central Java, Ministry of Public Work
- Cement Indonesia International University (UISI)
- Diponegoro University









STANDARD

- SNI 2847-2013
- ACI 318
- AASHTO T 140
- ASTM C 116

APPLICATION

- Harbor
- Arterial road
- Busway
- Toll road





Source: Analysis Results, 2023

Total CO2 Emission (Idle): 12,3 Ton/Hrs. Total CO2 Emission (Active): 0,82 Ton/Hrs.

- The total reduction in CO₂ emissions by all types of vehicles when traffic returns to normal is 98.3%.
- This research demonstrates that the use of RSC in road construction reduces carbon emissions and traffic congestion.

Loss of Fuel Consumption due to Traffic Congestion

			Average Cost Loss	
Type Vehicle	Units	Average Cost Loss For Each Vehicle in Non-Traffic Congestion	Average Cost Loss For Each Vehicle in Traffic Congestion	Average Cost Loss For Each Vehicle
Car	197	Rp232,263.00	Rp5,048,125.00	Rp4,815,862.00
Small Truck	122	Rp229,360.00	Rp4,445,924.00	Rp4,216,564.00
Big Truck	247	Rp474,240.00	Rp12,308,751.00	Rp11,834,511.00
Bus	4	Rp6,756.00	Rp146,448.00	Rp139,692.00
Motorcycle	1988	Rp528,808.00	Rp26,337,024.00	Rp25,808,216.00

The total cost lost due to loss of vehicle fuel consumption is Rp 46.814.845,-

Source: Analysis Results, 2023



Advantage

- Total Solution
- Minimize congestion
- Sustainable Construction
- Added Value & Total Cost Ownership
- 24 hour batching plant network

Guaranteed to be passed by vehicles at specified hours mentioning in the table:

SOLUTION PACKAGE	PERFORMANCE CRITERIA
SpeedCrete 3 hours	Setting time 3 hours
SpeedCrete 4 hours	Setting time 4 hours
SpeedCrete 8 hours	Setting time 8 hours
SpeedCrete 12 hours	Setting time 12 hours



POROUS CONCRETE

One of the innovative construction materials that is environmentally friendly because it can absorbs surface water into the ground

PARTNER

East Java Regional Residential Infrastructure Centre, Directorate General of Human Settlements, Ministry of Public Work

STANDARD

- ACI 522
- ACI 330R-01
- Special specifications for porous concrete pavement SKh-1.5.14 Directorate General of Highways 2022

TECHNICAL PROPERTIES

- Dimensions: 21 x 10,5 cm (H6 and H8)
- · Colour : green, red, natural
- Void: min 20%
- Strength: up to K250

• Percolation : 81-730 lt/mnt/m²

PAVING POROUS BY VUB




RESEARCH GOALS:

1. Showcase paving porous at national tourism strategic area Bromo-Tengger-Semeru (area of 457 m²).

There is no such application yet in the construction work of the East Java Regional Residential Infrastructure Center. This application will be the first time.

2. Product novelty: higher target compressive strength than existing product (K250) using PwrPro (SNI 8912:2020 (HE)).



Source: Analysis Results, 2023





POROUS CONCRETE

One of the innovative construction materials that is environmentally friendly because it can absorbs surface water into the ground

PARTNER

Directorate of Road and Bridge Engineering Development, Directorate General of Highways, Ministry of Public Work

STANDARD

- ACI 522
- ACI 330R-01
- Special specifications for porous concrete pavement SKh-1.5.14 Directorate General of Highways 2022

TECHNICAL PROPERTIES

- · Ready mix concrete
- Colour : red, dark grey, natural
- Void: min 20%
- Strength: up to 20 MPa
- Percolation: +250 lt/mnt/m²

THRUCRETE BY SBB



RESEARCH GOALS:

- 1. Support in order to improve the Special specifications for porous concrete pavement.
- 2. Showcase on the agenda: Exhibition of Electric Vehicles in the Context of Road Day 2022
- Porous Concrete has been applied with an area of 595 m² for 6 days.
- All requirements for acceptance according to the special specifications for porous concrete pavement SKh-1.5.14 of the Director General of Highways 2022 have been fulfilled.





PARTNER

Taiheiyo Cement Corporation (TCC) TAIHEIYO CEMENT

SOIL STABILIZATION


Our solution is a breakthrough soft soil problem by using cement based stabilizer agent. After applying the solution, the soil becomes impermeable, obtains high UCS and improves road durability.

STANDARD

- SNI 8460-2017
- ASTM D 2216-98
- ASTM D 698-00a
- SNI 03-3638-1994
- SNI 03-1744-1989

INDONESIAN SOFT SOIL & PEAT







Shale Clay 粘土質頁岩





Powder Type



Slurry Type

- Soft soil land in Indonesia deposit reaches 20 M hectare or 10% of total land area.
- The ground varies from area to area with different types, such as Peat soil, Shale clay, Marine clay, Expanded soil, etc., and
- We can harden almost all type of soft soil.
- However, it is important to use stabilizer agents and construction methods that are appropriate for each type of soil.
- As for the construction of Road, the durability of roads can be improved if solidifying the soft soil ground foundations properly.

One of the projects in Japan by CDM method (TCC Group)











Stabilizer agent was **customized** for the project. The solution was developed by SBI&PLP (SIG Group) and TCC Group.



HIGH PERFORMANCE CONCRETE USING HYDRAULIC CEMENT

(SNI 8912:2020)

According to Civil Engineering Research Foundation (CERP), HPC is concrete that has some or all of the following characteristics high/special: ease of placement, long term mechanical properties, early age strength, toughness, volume stability, extended service life in severe environments.


PARTNER

National Research and Innovation Agency (BRIN)



RESEARCH GOALS:

Development of High Performance Concrete using Hydraulic Cement so that performance is obtained in accordance with the quality requirements of SIG concrete subsidiaries with the quality criteria of FS 45 (3 days achieved 100%) for rigid pavement applications.




Based on the data from the research conducted, it was obtained the results of a concrete mix design using hydraulic cement which has high performance (optimal) and meets the Strength and Workability indicators.

Minimum flexural strength for concrete pavements

Description	Standard	Flexural Strength
Flexural strength at 28 days for concrete trial mix	SNI 4431:2011	47 (kg/cm²) FS 47
Flexural strength at 28 days for concrete pavements (production control)	SNI 4431:2011	45 (kg/cm²) FS 45

Source: Directorate of Road and Bridge Engineering Development, Ministry of Public Work, Dec 2012

Collaboration
between SIG – BRIN
HPC = fast track, in the
age of 3 days can be
achieved FS 45 using
Hydraulic Cement



Hydration of Normal Concrete versus High Performance Concrete

BEST PRACTICE





PERSON IN CHARGE PRODUCT CATALOG SIG


READYMIX CONCRETE			
Name	Phone Number		
Rizko	0812-8879-4633		
Destynia (Telesales)	0813-1655-1029		
Ifah (Telesales)	0878-8336-0292		

BULK CEMENT			
Name	Phone Number		
Dwi Andi Mahendra	0811-3385-586		
Rendra Jakadilaga	0811-3335-3695		
Taufan Maulana	0811-3486-885		

CUSTOMER CARE SIG		
Toll Free	Email	
0800-10-88888	cs@sig.id	









PT Semen Indonesia (Persero) Tbk.

South Quarter Tower A Lt. 19-20 Jl. RA Kartini Kav. 8, Jakarta Selatan 12430, Indonesia



DELIVERING ROAD SOLUTIONSIG PRODUCT & SOLUTION

SPEEDCRETE


SNI 2847-2013

SpeedCrete is one of SIG's innovative solutions – concrete with early strength and high performance, which can dry in hours. With SpeedCrete, repairing roads can be done in one night. SpeedCrete is made using state-of-the-art technology, applied using professional expertise and workmanship, and gives you superior strength and speed. It is proven to be highly effective in decreasing traffic jams while repairing high traffic area roads.



TOPCRETE

TopCrete is a high-performance ultra-thin white topping concrete work solution, has the ability as thin concrete construction, using laser screed & 3D profiler technology application and traffic management services carried out in hours and also can reduce total cost ownership. TopCrete thickness in the range of 7 to 10



COMFILPLAS

SNI 2847-2013

ComfilPlas is a mixture of mortar and foam as a lightweight fill material (density in the range of ±600-800kg/m3) for road foundations and bridge structure supports that have a light weight, produced by DynaPump a computerized mini batching plant and can pump up tp 150 M vertically and 250 M horizontally.

